

# Gasöl



ISO 8217/2010

Parameter	Unit	Limit	DMA	
			ISO	typical
Density at 15°C	kg/m <sup>3</sup>	Max.	860	860
Viscosity at 40°C	mm <sup>2</sup> /s	Max.	6	4
Micro Carbon Residue at 10% Residue	% m/m	Max.	0.2	0.2
Micro Carbon Residue	% m/m	Max.	---	---
Water	% V/V	Max.	---	---
Sulfur	% (m/m)	Max.	0.1	0.1
Total Sediment Existent	% m/m	Max.	-	-
Ash	% m/m	Max.	0.01	0.01
Vanadium	mg/kg	Max.	-	-
Aluminium + Silicon	mg/kg	Max.	-	-
Flash point	°C	Min.	60	60
Pour point, Summer	°C	Max.	0	0
Pour point, Winter	°C	Max.	-6	-6
Cloud point	°C	Max.	-	-
Calculated Cetane Index		Min.	40	40
Hydrogen Sulphide	mg/kg	Max.	2	2
Appearance		Clear & Bright		

A sulfur limit of 0.10% will apply in SOx Emission Control Areas designated by the International Maritime Organization. There may be local variations

NWB Nord - Westdeutsche Bunker GmbH, Billwerder Ring 21; 21035 Hamburg

gültig ab: 01.01.2020